

Back to [Clamp Meter](#) Main Page

**BK PRECISION®**

**Clamp-On Multimeter**

**Model 367A**

B+K Precision offers a wide variety of current clamps for safe non-invasive current measurement. Measure up to 2000A with these reliable, rugged instruments. All of B+K Precision clamps are much more than a current clamp offering the ability to measure, voltage resistance, capacitance and even frequency. Additionally, special features allow for the recording of minimum and maximum values, peak values, test diodes and for continuity. Any one of these products can be a total measurement solution.

- Measures up to 2000A
- Measures up to 1000V
- Low battery indication
- Accessories Supplied: Battery, Test Leads, Instruction Manual, Carrying Case

**Features**

	<b>367A</b>
AC Current	2000A
DC Current	2000A
AC Voltage	750V
DC Voltage	1000V
Resistance	40MΩ
Frequency	√
Capacitance	√
True RMS	√
Continuity	√
Diode	√
Count Resolution	4000
Bargraph	√
Data Hold	√
Peak Hold	√
Max Hold	
Range Hold	√
Max/Min	√
Relative	√
Auto Off	30 min.

**One Year Warranty**

**Accessories**

SUPPLIED: Battery, Test leads, Instruction Manual, Carrying Case  
 OPTIONAL: TL-1 Replacement Test Leads, TL-2A Deluxe Test Leads,  
 TL-3 Accessory Tip Kit (for TL-2A), TL-130A General Purpose  
 DMM Kit, PR-28A High Voltage Probe, CP-3 AC/DC  
 Current Clamp Adapter, LC-33 Carrying Case

Part No. 01CM367

**Specifications**

	<b>367A</b>
AC Current (using Clamp)	
Ranges	400A, 2000A
Resolution	100mA, 1A
Accuracy (50-60 Hz)	±(1.5% rdg + 5D)
Overload Protection	1200A
DC Current (using Clamp)	
Range	400A, 2000A
Resolution	100mA, 1A
Accuracy	±(1.5% rdg + 5D)
Overload Protection	1200A
AC Voltage (using test leads)	
Range	400mV, 4V, 40V, 400V, 750V
Resolution	100μV, 1mV, 10mV, 100mV, 1V
Basic Accuracy	±(1.5% rdg + 4D)
Overload Protection	1000V DC / 750V RMS
Input Impedance	10 MΩ
DC Voltage (using test leads)	
Range	400mV, 4V, 40V, 400V, 1000V
Resolution	100μV, 1mV, 10mV, 100mV, 1V
Basic Accuracy	±(0.5% rdg + 1D)
Overload Protection	1000V DC / 750V RMS
Input Impedance	10 MΩ
Resistance	
Range	400Ω, 4kΩ, 40kΩ, 400k, 4M 40MΩ
Resolution	0.1Ω, 1Ω, 10Ω, 100Ω, 1kΩ, 10kΩ
Basic Accuracy	±(1% rdg + 2D)
Overload Protection	500V DC / AC RMS
Frequency	
Range	100Hz, 1kHz, 10kHz 100kHz, 400kHz
Resolution	0.01Hz, 0.1Hz, 1Hz 10Hz, 100Hz
Accuracy	±(0.5% rdg + 3D)
Overload Protection	500V DC/AC RMS
Capacitance	
Range	4nF, 40nF, 400nF, 4μF, 40μF
Resolution	1pF, 10pF, 100pF, 1nF, 10nF, 100nF
Accuracy	±(1.5% rdg + 4D)
Overload Protection	500V DC/AC RMS
Jaw Opening	2.24" (57mm)
Display	3 3/4 digit LCD, 4000 count 9999 in Frequency 42 segment bar graph
Polarity	Automatic, "-" indicated
Measure Rate	2/sec.
Overrange Indication	"OL"
Operating Temperature	32° - 122°F, 70% RH (0° - 50°C)
Storage Temperature	-4° - +140°F, 80% RH (-20° - +60°C)
Power Requirements	One 9V battery, alkaline recommended type NEDA 1604A
Battery Life	500 Hours
Dimensions	10.8 x 3.6 x 1.7" (275 x 90 x 43mm)
Weight	18.3oz (519g)